

<div>Name</div> <div>Case color</div> <div>Type-model</div> <div>Panel</div> <div>Viewable image size</div> <div>Max view area (W x H)</div> <div>Optimum resolution</div> <div>Maximum resolution</div> <div>Aspect ratio</div> <div>Pixel pitch (mm)</div> <div>Dot/Pixel per Inch</div> <div>Brightness</div> <div>Contrast ratio</div> <div>Pixel response time</div> <div>Color gamut</div> <div>Anti-reflective</div> <div>Vertical frequency</div> <div>Horizontal frequency</div> <div>Viewing angle at 10:1 CR</div> <div>Stand</div> <div>Bezel width</div> <div>Dimensions (HxWxD)</div> <div>Power supply</div> <div>Weight</div> <div>Limited warranty<sup>4</sup></div> <div>Available date</div>	<div>L1951p Wide Flat Panel Monitor</div> <div>Business black</div> <div>2448-HB6</div> <div>TFT-LCD, twisted nematic (TN), CCFL backlight</div> <div>19.0" (481mm) diagonal</div> <div>16.07" x 10.05" (408.2mm x 255.2mm)</div> <div>1440x900 at 60Hz</div> <div>1440x900 at 75Hz (137MHz max pixel rate)</div> <div>16:10</div> <div>.285mm</div> <div>89 dpi</div> <div>250 nits or cd/m<sup>2</sup> (typical)</div> <div>1000:1 (typical)</div> <div>5ms (typical)</div> <div>72%</div> <div>Anti-reflective, anti-glare</div> <div>50 to 76Hz</div> <div>30 to 81kHz</div> <div>160° (+/- 80°) horizontal, 160° (+/- 80°) vertical</div> <div>Tilt and height adjustable stand</div> <div>Sides: 0.61" (15.6mm); top: 0.67" (17.1mm); bottom: 1.2" (30.5mm)</div> <div>14.56-17.71" H x 17.36" W x 6.11" D; 369.9-449.9mm H x 440.9mm W x 155.2mm D</div> <div>19 watts typical, 23 watts maximum, &lt;1 watts standby/suspend, universal, integrated (no external brick-like power supply)</div> <div>9.37 lb; 4.25kg</div> <div>3 year (includes backlight)</div> <div>October 2009</div>	<div>Features</div> <div>• Widescreen 19-inch monitor</div> <div>• Supports WXGA+ 1440x900 resolution</div> <div>• Ergonomic stand tilts and provides a 3.1" (80mm) range height adjustment for comfortable viewing</div> <div>• Includes dual input connection for attachment to two systems concurrently (analog and digital)</div> <div>• Reduces mercury content by 50% and arsenic free glass</div> <div>• Up to 70% recycled packaging materials</div> <div>• Privacy Filter Slot</div> <div>• Microsoft® Windows® 7 certified</div>
<div>VESA-compliant<sup>2</sup></div> <div>Power management</div> <div>Ergonomics</div> <div>Emission standards</div> <div>Environmental</div>	<div>VESA DDC2B/CI, VESA DPMS-compliant</div> <div>ENERGY STAR® 5.0</div> <div>ISO 9241-307</div> <div>MPR-2, MPR-3A, FCC Class B</div> <div>TCO (TCO Displays 5.0), WEEE, RoHS,</div> <div>EPEAT™ Gold rating</div>	<div></div> <div>ThinkVision L1951p Wide Monitor</div>
<div>Preset resolutions</div>	<div>VGA: 640x350, 640x480, 720x400</div> <div>SVGA: 800x600, 832x624</div> <div>XGA: 1024x768, 1152x864</div> <div>SXGA: 1280x1024</div> <div>WXGA: 1280x720, 1360x768</div> <div>WXGA+ 1440x900</div>	
<div>Presets / user settings</div>	<div>Standard presets: 27;</div> <div>user settings: 20</div>	
<div>Viewing adjustments</div> <div>Rotating screen</div> <div>On screen display</div> <div>Control features</div> <div>Multiple input</div> <div>Monitor connectors</div>	<div>Tilt: 20° back, -3° forward; lift: 3.1" (80mm); detachable stand</div> <div>None</div> <div>On screen display with digital user controls (8 languages)</div> <div>Direct access (buttons on front) for automatic image setup</div> <div>Dual input (two different PCs attach to two different connectors; one PC shows image; select via button)</div> <div>(1) VGA 15-pin D-shell, analog, blue</div> <div>(2) Digital Visual Interface (DVI-D), digital, white, <b>HDCP-compliant</b></div> <div>(1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter</div> <div>(2) detachable, DVI-D at each end, digital, 1.8 meter</div> <div>Wall or desk mounting using the Radial Arm<sup>9</sup> or third-party accessories meeting the VESA FPMPI® (100mm mount)</div> <div>Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)</div>	
<div>Signal cables</div>		
<div>Mounting features</div> <div>Security</div>		
<div>Ship group</div>	<div>Monitor, attached stand, Setup poster, Safety and Warranty Information, CD with multilingual User's Guide and monitor installation files, 1.8 meter analog signal cable, 1.8 meter digital signal cable, 1.8 meter black power cord</div>	
<div>Limited Warranty</div> <div>➤ 3 year limited warranty<sup>4</sup></div> <div>➤ International Warranty Service<sup>5</sup></div> <div>➤ Rapid Replacement Service at 1-800-426-7378</div> <div>➤ Replacement normally arrives in two business days, excluding holidays</div> <div>➤ Lenovo pays all shipping costs for valid warranty claims<sup>6</sup></div> <div>➤ Service upgrade options:<sup>7</sup></div> <div>• 3 year, on site exchange, Mon-Fri 9-5 with next day response (ThinkPlus™ part number 41C9209)</div> <div>• 3 year, on site exchange, 7 day x 24 hr with 4 hour response (41C9212)</div> <div>• 4 year, on site exchange, Mon-Fri 9-5 with next day response (41C9233)</div> <div>• 4 year, on site exchange, 7 day x 24 hr with 4 hour response (41C9216)</div> <div>• 4 year, mail exchange (51J0589)</div> <div>• 5 year, mail exchange (51J0590)</div> <div>➤ 24x7<sup>8</sup> day toll-free support for warranty issues during the warranty period<sup>4</sup></div>		
<div>Accessories</div> <div>ThinkVision Soundbar</div> <div>45K1263</div> <div>Kensington® MicroSaver® Cable Lock</div> <div>73P2582</div> <div>Kensington Twin Head Cable Lock</div> <div>45K1620</div> <div>ThinkPad Convertible Monitor Stand</div> <div>40Y7620</div> <div>ThinkVision TFT Radial Arm<sup>9</sup></div> <div>19K4464</div> <div>See details at <a href="http://www.lenovo.com/support/monitoraccessories">www.lenovo.com/support/monitoraccessories</a></div> <div>See all monitors at <a href="http://www.lenovo.com/thinkvision">www.lenovo.com/thinkvision</a></div>		